

RFC-031: Module registry and construction context for wtf

- **Status:** draft, open for review
- **Author:** J. Appleseed
- **Target:** wtfutil/wtf at bb838c1
- **Affects:** app/widget_maker.go, wtf/, every package under modules/

1. Motivation

Adding a module requires editing both the imports and the `MakeWidget` switch in `app/widget_maker.go:9–379`. Contributors adding unrelated modules can conflict in this file. The switch also has to know each module's constructor arguments, including whether it needs pages or build metadata.

This RFC replaces the switch with a registry: each module registers a function that creates its widget under a type name. `MakeWidget` looks up that function and calls it. A shared `ModuleContext` gives constructors the same set of application values.


New modules would need a registration function and an import in `modules/all.go`, without changes to the `app` package. Modules in other repositories could use the same registration mechanism.

2. Current design

`MakeWidgets` calls `MakeWidget` for each entry in `wtf.mods`. `MakeWidget` returns `nil` for missing or disabled entries. Otherwise, it selects the module using `moduleConfig.UString("type", moduleName)`, builds its settings, and calls its constructor (`app/widget_maker.go:98–399`).

Constructors take either the application and redraw channel, or those values plus pages. The system module also takes build metadata. Modules can pass `nil` for pages to the shared view code; six modules also store pages for their own dialogs.

An unrecognized type produces an unknown widget that displays an error (`modules/unknown/widget.go:29`).



3. Proposal

3.1 Registry API

Add a map from module type names to factory functions (functions that create widgets) in the `wtf` package, next to `wtf/wtfable.go`.

```

package wtf

// ModuleFactory builds one widget from its configuration.
type ModuleFactory func(
    ctx *ModuleContext,
    moduleName string,
    moduleConfig *config.Config,
    globalConfig *config.Config,
) Wtfable

var registry = map[string]ModuleFactory{}

// RegisterModule records a factory under a module type name.
func RegisterModule(name string, factory ModuleFactory) {
    registry[name] = factory
}

// LookupModule returns the factory registered for a module type name.
func LookupModule(name string) (ModuleFactory, bool) {
    factory, ok := registry[name]
    return factory, ok
}

```

Only RegisterModule writes to the map. Keeping the registry in wtf lets modules register without importing app, which would create an import cycle.

3.2 Factory signature and ModuleContext

Group the application, pages, and redraw channel in one struct:

```

package wtf

// ModuleContext carries the application-owned collaborators that a module
// may need while it is being constructed.
type ModuleContext struct {
    TViewApp *tview.Application
    Pages    *tview.Pages
    RedrawChan chan bool
}

```

Each module's NewWidget takes this context and its settings, using the fields it needs. For clocks:

```

package clocks


func NewWidget(ctx *wtf.ModuleContext, settings *Settings) *Widget {
    widget := Widget{
        TextWidget: view.NewTextWidget(
            ctx.TViewApp, ctx.RedrawChan, ctx.Pages, settings.Common,
        ),

        settings: settings,
        dateFormat: settings.dateFormat,
        timeFormat: settings.timeFormat,
    }

    widget.clockColl = widget.buildClockCollection()

    return &widget
}

```



3.3 Registration and imports

Each module registers its factory in `register.go`. Go runs the imported package's `init()` function once before `main`:

```
package clocks

func init() {
    wtf.RegisterModule("clocks", func(
        ctx *wtf.ModuleContext,
        moduleName string,
        moduleConfig *config.Config,
        globalConfig *config.Config,
    ) wtf.Wtfable {
        settings := NewSettingsFromYAML(moduleName, moduleConfig,
globalConfig)
        return NewWidget(ctx, settings)
    })
}
```

A new `modules/all.go` imports every built-in module. The `_` imports run each package's initialization without using its exported names:

```
// Package modules imports every built-in module for its registration
// side effect.
package modules

import (
    _ "github.com/wtfutil/wtf/modules/airbrake"
    _ "github.com/wtfutil/wtf/modules/asana"
    _ "github.com/wtfutil/wtf/modules/azuredevops"
    // ... one line per built-in module ...
    _ "github.com/wtfutil/wtf/modules/zendesk"
)
```

`main.go` blank-imports modules. The app package no longer needs module imports.

3.4 Unknown types

`MakeWidget` returns an error if no factory matches the configured type:

```

func MakeWidget(
    ctx *wtf.ModuleContext,
    moduleName string,
    config *config.Config,
) (wtf.Wtfable, error) {
    moduleConfig, _ := config.Get("wtf.mods." + moduleName)
    if moduleConfig == nil {
        return nil, nil
    }

    if enabled := moduleConfig.UBool("enabled", false); !enabled {
        return nil, nil
    }

    typeName := moduleConfig.UString("type", moduleName)

    factory, ok := wtf.LookupModule(typeName)
    if !ok {
        return nil, fmt.Errorf(
            "module %q: no module registered for type %q", moduleName,
            typeName,
        )
    }

    return factory(ctx, moduleName, moduleConfig, config), nil
}

```

MakeWidgets collects these errors. NewWtfApp prints them and exits, following ModuleValidator.Validate (app/module_validator.go:27–41). Unknown types become startup errors, and the unknown package is deleted.

3.5 Tests

Update app/widget_maker_test.go to pass a *wtf.ModuleContext and check the returned error. Keep the existing widget-type assertions. Tests can also register fake factories to check MakeWidget without constructing real modules.

4. Migration plan

Add the registry, ModuleContext, and revised MakeWidget, keeping the switch as a fallback until all modules have been converted. This lets the application keep working during migration.

Convert roughly ten modules per PR: update NewWidget, add register.go and a blank import, and remove the module's switch case.

For system, move buildDate() and buildVersion() (app/widget_maker.go:403–437) to an exported package that the module can call directly.

After converting all modules, remove the switch, its imports, and the unknown package. Update generator/textwidget.go:40 to tell authors to add an import to modules/all.go.

5. Alternatives considered

- Keep the switch: it is easy to read, but app still needs to import and construct every module.
- Generate the switch with `go:generate`: this removes manual edits but adds a generation step and a file that contributors must keep up to date.
- Use a central map: this simplifies the switch but keeps the shared list and module imports in app.
- Load modules with Go's `plugin` package: this requires separate builds and matching toolchain and dependency versions. It also lacks Windows support.

6. Open questions

- Should the registration function be called `RegisterModule` or `Register`?
- Should the import list live in `modules/all.go` or `app/modules.go`?
- Should `ModuleContext` be a struct or an interface? The struct is simple, but would an interface help tests?
- Should `MakeWidgets` return `([]wtf.Wtfable, []error)` so callers can handle partial failures?
- Should a lint check keep the import list alphabetized?
- Should each migration PR convert five modules or ten?